WORLDWIDE PERFECTION
SPRAY TROLLEY/ROBOT

The spray robot of Buitendijk-Slaman is easy to use. The control software is very users friendly and developed by our own development department. Thanks to our own engineering, we can provide customized settings at minimal cost. This spray robot guarantee security, robustness and durability. **The transportation trolley** follows with a conductor the heating pipes lying on the concrete path. Detecting when to stop will be done by a arm that slides over the pipe rail. The car has its own easy control unit that counts the paths and if necessary he can skip a path. The transportation trolley is mounted a hose rail. The hose provides the spray water for the spray robot.

buitendijkslaman

worldwide internal transport

SPECIFICATIONS
SPRAY TROLLEY/ROBOT

		SPRAY TROLLEY	SPRAY ROBOT	TRANSPORTATION TROLLEY
Dimensions	:	1.550 x 650 mm.	1.650 x 550 mm.	1.600 x 2.000 x 1.750 mm.
Drive	:	650 Watt motor.	650 Watt motor.	150 Watt motor.
Speed	:	Adjustable Max.± 90 meter p/min.	From ± 25 till 90 meter p/min.	2 meter p/min.
Frame	:	Galvanised.	Galvanised.	Galvanised.
Battery	:	Full traction-batteries 120 Amp. (10h).	Full traction battery 110 Amp. (24V).	Full traction battery 110 Amp. (24V).
Centre to centre	:	From c.t.c.425 mm.	From c.t.c.425 mm.	From c.t.c.425 mm.
Languages	:	English, Dutch, Polish up to 6.	English, Dutch, Polish up to 6.	English, Dutch, Polish up to 6.
Lifting wheels	:	By hand.	Hydraulic nylon wheels.	Manual.
Spray boom	:	16 positions whit adjustable nozzles (height 2100mm.).	Stainless steel with adjustable side sprayers (blue tips), double front sprayers (blue tips), manometer and pressfilter.	-
Battery indicator	:	Yes.	Yes.	Yes.
Error alarm	:	Yes .	Yes.	Yes.
Hose reel	:	For max 150 meter 1/2" hose.	For max 160 meter 1/2" hose.	For max 160 meter 1/2" hose.
Hose guide	:	Yes, automatic.	Yes, automatic.	Yes, automatic.
Hose	:	100 meter hose 1/2" 80 bar.	100 meter 1/2" HP spray hose 80 bar.	-
Controle unit	:	Touch control.	Touch control.	Touch control.

SEVERAL ADVANTAGES:

- Spray robot setting via control panel transortation trolley
- GSM module to receive notifications from transortation trolley
- Spray gun
- Multiple spray masts
- Robot running in inox plate work
- Pump exit

The spray trolley, sprayrobot and transortation trolley of Buitendijk-Slaman are very user-friendly operating by our own developed software. Through our own engineering staff, we can provide tailor-made again at minimal cost. This spray trolleys are safety, robustness and durability guarantees.

Simple control cabinet spray trolley

Barn for spraying mast

Simple control cabinet spray robot

CMW Horticulture Ltd
Stonepit Road, South Cave, Brough
East Yorkshire, HU15 2BZ
Phone: 01430 422222
Email: enquiries@cmwhorticulture.co.uk

If you require more information please feel free to contact us.

buitendijkslaman

worldwide internal transport

Buitendijk & Slaman bv
Zernikestraat 2 | P.O. Box 119
2665 ZJ Bleiswijk
The Netherlands

P. +31 (0)10 521 63 77
F. +31 (0)10 521 90 73
info@buitendijk-slaman.nl
www.buitendijk-slaman.nl